


Add:2nd Floor,No.183, Ting Yuan Road, Xin Gang Dong Road, Haizhu District, Guangzhou

To :  
**Company: China Direct**  
**10 rue Claude Bernard, Z.I. Ducos**  
**98800 Noumea, New Caledonia**  
**Mrs Helene Andres**  
**(687)76 11 30**

### data sheet

Code	Description	Image	Detail
01	<p style="text-align: center;"><b>Single - CANTILEVE R RACKS</b></p> <p><b>L1400*W1800 *H3620mm</b></p>		<p>1.Material: Cold-rolled Steel .</p> <p>2.Surface Treatment: Acid washing-Epoxy Electrostatic Spray.</p> <p>3.Color: Blue &amp; orange.</p> <p>5.3 layers including base.</p> <p>6.Loading capacity: 1500kg/layer.</p> <p>7.Size :L1400*W1800*H3620mm</p> <p>8.Specifaction: Upright(250*80*3mm) Base(250*80*3mm Double "C" Type            Arm(400*80*50*3mm) Double "C" Type            Bracing bar ( 50*25*1.5 )</p>

#### 1.Design Standard

JB/T 5323-91 Technical specification of steel frame shelf;  
 ZBJ83015-89 Code for design of high-rise shelf warehouses;  
 FEM10.202 European material handling association code for design of steel frame shelves;

#### 2.Product technical features

The column and the horizontal brace, the inclined brace and the bottom plate are connected by bolts, and the bolts are all 4.8 grade galvanized high-strength bolts;

Formed parts are rolled by the factory, the rigidity, strength are in line with the industry standards of the Ministry of Machinery;

#### 3.Surface treatment

The surface of all parts of the shelf is derusting - degreasing - phosphating, and then the epoxy resin electrostatic powder spraying treatment, the coating thickness is 60~80 microns, and the temperature is 180°C dry, and the use of 2H pencil test without scratches;

The adhesion of electrostatic spray powder reaches the level 0 requirement of GB92865-88 standard;

Hardness(abrasion resistance) is more than 100 times of ordinary nitrocellulose paint, the 2 II GB6739-86 standard requirements;

Corrosion resistance test (hydrochloric acid test) GB1171-91 more than 500 hours.

#### 4.Technical deviation

The maximum allowable deflection of the column is 1/1000 and the safety factor is 1.2.

#### 5.Strength

Strength index of shelf profiles(N/mm<sup>2</sup>): Tensile resistance, compression resistance, bending resistance 205, shear resistance 120, end face pressure 310;

Strength index of shelf welds(N/mm<sup>2</sup>): Butt weld compression 120, tensile 175, bending 120; Fillet weld resistance to compression, tension and resistance 140.

6.Color: Standard color: blue - orange(- yellow - gray white).