

MODELE VALLON DORE SUD
CRUE DECENNALE

POINT	PK (Km)	DEBIT (m3/s)	NIVEAU (m)	VITESSE (m/s)	CHARGE (m)
P5d	-0.395	14.00	41.39	2.10	41.62
P5c	-0.285	19.00	33.64	2.84	34.05
P5b	-0.180	19.00	25.78	1.22	25.86
P5a	-0.095	19.00	20.16	1.69	20.31
P5	0.000	19.00	14.20	0.93	14.24
Inj1	0.080	20.00	12.22	0.96	12.26
P6	0.160	20.00	10.70	0.39	10.71
O5	0.162	20.00	10.70	0.39	10.71
O5av	0.165	20.00	9.99	1.65	10.13
P7	0.360	20.00	5.35	0.95	5.40
Inj2	0.362	25.00	5.28	1.40	5.38
P8	0.640	25.00	2.52	0.39	2.53
O6	0.642	25.00	2.52	0.39	2.52
O6av	0.645	25.00	2.04	0.81	2.07
Inj3	0.880	29.00	1.48	0.27	1.48
Aval	1.140	29.00	1.40	0.15	1.40

CRUE CENTENNALE

POINT	PK (Km)	DEBIT (m3/s)	NIVEAU (m)	VITESSE (m/s)	CHARGE (m)
P5d	-0.395	24.00	41.61	2.34	41.89
P5c	-0.285	32.00	34.02	3.14	34.52
P5b	-0.180	32.00	25.96	1.47	26.07
P5a	-0.095	32.00	20.30	1.98	20.50
P5	0.000	32.00	14.50	1.00	14.55
Inj1	0.080	35.00	12.46	1.16	12.53
P6	0.160	35.00	11.00	0.51	11.01
O5	0.162	35.00	11.00	0.51	11.01
O5av	0.165	35.00	10.18	1.64	10.32
P7	0.360	35.00	5.52	1.25	5.60
P8	0.640	42.00	2.68	0.55	2.70
O6	0.642	42.00	2.68	0.55	2.70
O6av	0.645	42.00	2.27	0.90	2.31
Inj3	0.880	49.00	1.58	0.41	1.58
Aval	1.140	49.00	1.40	0.25	1.40